+12 ok to enten. glysp.

FROOM et al Appl. No. 09/752,834 January 30, 2004

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1 (currently amended). A process for the production of lower aliphatic esters which comprises reacting a lower olefin selected from the group consisting of ethylene and propylene with a C₁ to C₄ carboxylic acid in the vapour phase in the presence of a heteropolyacid catalyst selected from the group consisting of 12-tungstophosphoric, 12-molybdophosphoric, 12-tungstosilicic and 12-molybdosilicic acid, wherein a) the reaction is carried out in a plurality of reactors set up in series, and b) the feedstock has no more than 0.1 ppm of metallic or metal compound impurities prior to being brought into contact with the heteropolyacid catalyst.

2 (original). A process as claimed in claim 1, wherein the feedstock has no more than 0.1 ppm of metals and/or metal compounds, prior to being brought into contact with the heteropolyacid catalyst.

3 (original). A process as claimed in claim 1, wherein the feedstock has less than 0.01 ppm of metals and/or metal compounds, prior to being brought into contact with the heteropolyacid catalyst.

4 (original). A process as claimed in claim 1, wherein the feedstock is rendered substantially free of metallic or metal compound impurities which arise from the

FROOM et al Appl. No. 09/752,834 January 30, 2004

corrosion of equipment, or which result from any water or acetic acid reactant used in the reaction.

5 (original). A process as claimed in claim 4, wherein the metallic or metal compound impurities which arise from the corrosion of equipment comprise: iron, chromium, nickel and/or molybdenum.

6 (original). A process as claimed in claim 4, wherein the metallic or metal compound impurities which result from any water or acetic acid reactant used in the reaction comprise sodium, potassium and/or calcium.

7 (original). A process as claimed in claim 1, wherein the metallic or metal compound impurities are removed from the feed to the reactor using a guard bed and/or a vaporiser.

8 (original). A process as claimed in claim 7, wherein the guard bed is in the form of an ion-exchange resin.

9 (original). A process as claimed in claim 7, wherein the guard bed comprises amorphous aluminosilicates, clays, zeolites, aluminophosphates, silicoaluminophosphates, metalaluminophosphates or supported heteropolyacids.

FROOM et al Appl. No. 09/752,834 January 30, 2004

10 (original). A process as claimed in claim 1, wherein the metallic or metal compound impurities are removed from the feed to the reactor using a vaporiser which employs demister pads and/or a heavy ends take-off at the base of the vaporiser to remove said impurities.

11 (original). A process as claimed in claim 10, wherein fresh acid is introduced into the vaporiser to scrub out the metallic or metal compound impurities.

12 (canceled).

13 (original). A process as claimed in claim 1, wherein said lower olefin is ethylene.

14 (previously presented). A process as claimed in claim 1, wherein the mole ratio of olefin to the C_1 to C_4 carboxylic acid in the reactant gases fed to the first reactor is in the range of from 1:1 to 18:1.

15 (original). A process as claimed in claim 1, wherein said plurality of reactors set up in series is in the form of one long reactor which has a plurality of catalyst beds set up in series.